

Electronic Dual Level Switch

BLS3000

Features

- ▶ Signal resolution: 1/5" (5 mm)
- ▶ Redundant measurement system ensures reliable output
- ▶ Total length (L0): 9.8"-39.4" (250 mm-1000 mm)
- ▶ One or two switch points
- ▶ Analog output: 4 - 20 mA or 0 - 10 V
- ▶ Rotatable 320° display & electrical connection
- ▶ Easy menu navigation

Applications

- ▶ Level control for:
 - ▮ Hydraulics
 - ▮ Lubrication system
 - ▮ Cooling



General Specifications*

Sensor element:	Reed switch	Digital display:	4-digit 14-segment LED display, red, digit height 0.35 inches (9 mm)
Materials:		Error display:	LED RED and alphanumeric display
Wetted parts:		Analog output:	4-20 mA
Stem (Fitting, Tube):	Stainless steel 316Ti	Current output:	max. RI = (Ub-12V) / 20 mA
Float:	NBR (BUNA-N) foam	Load:	RI = 600 Ohm at Ub = 24 V DC
Seals:	FKM, EPDM or NBR (BUNA-N)	Scanning rate:	2 ms
Electronic housing:	Stainless steel 316Ti, PBT, elastomer	Voltage output:	0 to 10 V DC
Operating elements:	3 easy-response push-buttons	Rating:	max. 10 mA
Enclosure rating:	Type 1 / Type 4X (IP65) / Type 6 (IP67)	Adjustment range:	25% to 100% f. s.
Protection class:	III	Units:	
Electrical connection:	Plug M12 x 1, 4-pin / 5-pin / 8-pin (depending on Output selection)	Distance:	% , mm, cm, m, inch, feet,
Process connection:	See Product Configurator for process connection options (page 2)	Volume:	liter, m ³ , gallon
Float BN17:		Transistor switching outputs:	
Density medium:	min. 0.02 lb/in ³ (0.60 g/cm ³)	Switching function:	Normally open/normally closed, standard / window mode and adjustable functions
Depth of immersion:	0.59" ± 0.07" (15 ± 2 mm) (water) 0.74" ± 0.07" (19 ± 2 mm) (oil 0.75) Ø0.70", height 0.98" (Ø17.8 mm, height 25 mm)	Switching output:	PNP
Dimensions enclosure:	1.6 Ø x 4.5 inches (41 x 110 mm) For 1/2" NPT (without M12 connector or probe). Contact factory for other sizes.	Adjustment range for switching point and hysteresis:	0 % to 125 % f. s.
Weight:	Approx. 0.77 lb (350 g) (for G1/2" size and 250 mm L0, for exact weight, contact factory)	Switching frequency:	Max. 100 Hz
Total length (L0):	9.8" (250 mm), 14.6" (370 mm), 16.1" (410 mm), others on request up to 39.4" (1000 mm)	Load	Max. 500 mA, short-circuit proof
Accuracy:	± 1 digit (without turbulence) including temperature influence and repeatability	Delay	0.0 s to 50 s adjustable
Resolution:	1/5" (5 mm)	Status display(s):	LED(s) red
Max. pressure:	43.5 psi (3 bar)	EMI:	EN 61000-4-2 ESD 4 kV CD / 8 kV AD
Temperature range:			EN 61000-4-3 HF radiated 10 V/m
Medium:	-13 °F to +176 °F (-25 °C... +80 °C)		EN 61000-4-4 Burst 2 kV
Ambient/Operating:	-4 °F to +158 °F (-20 °C... + 70 °C)		EN 61000-4-5-Surge 1/2 kV
Storage:	-22 °F to +176 °F (-30 °C... + 80 °C)		EN 61000-4-6 HF conducted 10 V
Power supply:	15 to 28 V DC, reversed polarity protected (SELV, PELV)	Shock resistance	DIN EN 60028-2-27 50 g (11 ms)
Power consumption:	Approx. 50 mA (without load) Approx. 80 mA (Output Code 6)	Vibrations resistance	DIN EN 60028-2-26 20 g (10...2000 Hz)
		Approvals:	cULus ¹


* See product configurator for additional options.

1) Conditions of use: 140 °F (60 °C) max. ambient, power supply max. 28 V DC

Electronic Dual Level Switch

BLS3000

Technical Drawings



Product Configurator

Example BLS3 1 6 X M 14.6Z

Series:

BLS3

Series BLS3000, electronic dual level switch

Output:

- 1 Dual switch point
- 2 Single switch point plus 4-20mA
- 3 Single switch point plus 0-10V
- 4 Dual switch point plus 4-20mA
- 5 Dual switch point plus 0-10V
- 6 Dual switch point (1x NO SPST / 1x NC SPST), non UL

Process Connections:

- 2 G1/2" male, with seal (seal code V, E or B)
- 3 1/2" NPT male, without seal (seal code X)
- 5 G3/4" male, with seal (seal code V, E or B)
- 6 3/4" NPT male, without seal (seal code X)
- A G1" male, with seal (seal code V, E or B)
- B 1" NPT male, without seal (seal code X)
- C 1 1/4" NPT male, without seal (seal code X)
- H M20 x 1.5 mm male, with seal (seal code V, E or B)
- I¹ 7/8-14 UNF (SAE 10) male, (seal code V, E or B)
- J¹ 1 1/16-12 UN (SAE 12) male, (seal code V, E or B)

Note: 1. Subject to minimum order quantity of 10 pieces; consult factory for lead time.
 2. Mating connector not included with unit; mating connectors are available and can be ordered as an accessory.
 3. Custom length available up to 39.4" (1000 mm); minimum quantities may apply.
 4. Available only for G & M thread.
 5. Available only for NPT, UNF & UN thread.

6. See Cable Connectors & Accessories for more options.

Total Sensor Length L0³:

- 0250M⁴ 250 mm (process con. code 2, 5, A & H)
- 0370M⁴ 370 mm (process con. code 2, 5, A & H)
- 0410M⁴ 410 mm (process con. code 2, 5, A & H)
- 1000M⁴ 1000 mm (process con. code 2, 5, A and H)
- 09.8Z⁵ 9.8 inch (process con. code 3, 6, B, C, I, & J)
- 14.6Z⁵ 14.6 inch (process con. code 3, 6, B, C, I, & J)
- 16.1Z⁵ 16.1 inch (process con. code 3, 6, B, C, I, & J)
- 39.4Z⁵ 39.4 inch (process con. code 3, 6, B and C)

Electrical Connection:

M² M12 x 1 mm (4 or 5 pin)