

Temperature Transmitter

BT1

Features

Fast response: Compact stainless-steel construction delivers fast-response temperature sensing and drift-resistant performance in aggressive media and high-cycle environments.

Flexible outputs: Available with CAN J1939, CANopen, and analog output options for modern platforms.

Hazardous-location approvals: Intrinsically safe CSA and ATEX options are available for hazardous locations.

Applications

- ▶ Hydraulic and Pneumatic Systems
- ▶ Heavy Mobile Equipment
- ▶ OEM Factory Automation
- ▶ Wellhead Tubing, Casing & BOP
- ▶ Fracking Trucks
- ▶ Natural Gas Compressors & Turbines
- ▶ Mobile Hydraulics



Image for marketing purposes only







Performance Characteristics			
Temperature Range	From -65°F to 392°F (-55°C to + 200°C)	Ambient temperature range	- 40 °C ... 85 °C (-40 °F ... 185 °F)
Probe Length	1.0" to 4.0" (custom lengths available)	Storage temperature range	- 40 °C ... 85 °C (- 40 °F ... 185 °F)
Pressure Port Thread	G1/4 Form E, 1/4" - 18NPT, 7/16"-20 UNF, 9/16"-18 UNF	Humidity	0 ... 100 % r. h., non-condensing
Electrical Connector	EN 175 301-803-A /-C; M12x1 (S763-4); Deutsch DT04-3P; Packard Metri-Pack; cable outlet	Shock protection	EN/IEC 60068-2-32 (1 m free fall)
Protection grade	IP65/IP67 (depending on connector)	Vibration	20 g / 3 axes to EN/IEC 60068-2-6
Material of Construction	316 Stainless Steel	EMI/RFI emission	EN 61326-1:2013-section 7 EN 61326-2-3:2013
Approvals	ATEX, IECEx, CSA	EMI/RFI susceptibility	EN 61326-1:2013 - section 6 EN 61326-2-3:2013
Accuracy (25°C)	+/- 1 % FS	Material of wetted parts	Stainless steel
Overall accuracy	+/- 2 % FS	Media temperature range	- 40 °C ... 200 °C (-40 °F ... 392 °F)
Long-term stability	±0.1 % FS per year in referential condition	Measuring element	1 x PT100, class B
Max. operating pressure	10,000 psi		

Electrical Data			
Certifications	CSA/ATEX (Current Output)	CSA (Voltage Output)	CSA (Ratiometric Output)
Output signal	4 ... 20 mA	0/1 ... 5 V DC; 0/1 ... 6 V DC; 0/1 ... 10 V DC	0,5 ... 4,5 V DC ratiometric
Supply voltage (DC)	CSA : 12 ... 27 V ATEX : 20 ... 27 V	10 ... 27 V (Vout x ... 5 V) 10 ... 27 V (Vout x ... 6 V) 15 ... 27 V (Vout x ... 10 V)	5 V DC +/- 5 %
Load resistance	< (Vcc-10 V)/20 mA	> 5 kOhm	> 2,5 kOhm
Current consumption	3,6 ... 21,4 mA	7 mA typ.	7 mA typ.
Response time	< 2 ms	< 2 ms	< 2 ms
Reverse and overvoltage protection	yes	yes	yes

Temperature Transmitter

BT1





Electrical connection ¹

MIL-C-26482				M12x1 (S763)				EN 175 301-803-A				Cable			
															
Output	Pin A	Pin B	Pin C	Output	Pin 1	Pin 3	Pin 4	Output	Pin 1	Pin 2	Pin 3	Output	Red	Black	White
Volt	+	-	Vout	Volt	+	-	Vout	Volt	+	-	Vout	Volt	+	-	Vout
mA	+	-	nc	mA	+	-	nc	mA	+	-	nc	mA	+	-	

Process connection

Process connections (standard) ¹ G1/4 Form E, 1/4"-18NPT, 7/16"-20 UNF, 9/16"-18 UNF

Temperature tip ¹ Stainless steel tip with diameter 6 mm (0.24")
 10 mm ... 500 mm



¹ Order on request

² Lx = Probe Length, where x = 1,2,3,4 inches respectively

Temperature Transmitter

BT1

Product configurator

	Example	BT1	CS	-5	-KZ	F	-L1	P8	T2
--	---------	-----	----	----	-----	---	-----	----	----

Base Model

BT1Barksdale Temperature Transmitter

Approvals

CS

CSA, Standard application

AT

ATEX, Standard application

CH

CSA, Hydrogen application

AH

ATEX, Hydrogen application

Electrical Output

-3

Voltage Output

-4

Ratiometric Output

-5

Current Output

-6

Custom Voltage Output

Temperature Range³

	°C	°F
V	-55	-65
N	-50	-60
K	-40	-40
H	-30	-20
G	-20	0
D	-10	20
0	0	32
1	10	50
2	20	70
3	30	85
4	40	100
5	50	120
6	60	140
7	70	160
8	80	180
9	90	200
X	100	210
Y	110	230
Z	120	250
B	130	265
E	140	285
M	150	300
J	180	355
P	200	392

Electrical Connection

T2

MIL-C-26482

T4

M12x1 (S763-4)

T5

EN 175 301-803-A

H3

Cable 4P

TC

Custom

Process Connection

P1

G 1/4, washer seal, Male

P3

7/16-20 UNF

P8

1/4" -18 NPT

PC

Custom

Probe Length

-L1

1 Inch

-L2

2 Inch

-L3

3 Inch

-L4

4 Inch

Temperature Unit

F

Fahrenheit

C

Celsius

K

Kelvin

³ Consult the factory for a custom range.