

# Transmitter

## BiT – Barksdale Intelligent Transmitter *Series H455E, 455E, 452E, 454E*

### Features

- ▶ Intrinsic safety certification with ATEX, IECEx and CSA approvals
- ▶ Lightweight, compact and all-welded rugged stainless steel construction
- ▶ High performance sensors
- ▶ Optional HART® communication protocol with diagnostics & field calibration, reducing maintenance time and cost; 10:1 turndown ratio for re-ranging, maintaining high accuracy and allowing one part number for multiple pressure ranges
- ▶ High accuracy:  $\pm 0.1\%$  and  $0.25\%$  FSO, (L,H,R)
- ▶ Additional CSA certification for ordinary locations
- ▶ Factory sealed IP66 & IP67 and NEMA 4X enclosure
- ▶ CE, NACE compliant and superior EMC/EMI protection
- ▶ RoHS / REACH Compliant

### Applications

- ▶ Drilling rig control & monitoring instrumentation
- ▶ Drilling and frac offshore equipment skids
- ▶ Production control systems
- ▶ Chemical injection systems
- ▶ Oil & gas pipelines
- ▶ Petrochemical plants
- ▶ Refineries
- ▶ Gas and oil fired power plants
- ▶ Hydraulic power units
- ▶ Gas transfers for fuel systems
- ▶ O&G process pumps
- ▶ Gas compressors
- ▶ Generators and turbines



### General Specifications\*

<b>Accuracy</b> including Linearity, Hysteresis and Repeatability: at 75°F, Typical	$\pm 0.1\%$ of Calibrated FSO (Option [-A1]) $\pm 0.25\%$ of Calibrated FSO (Standard) $\pm 0.5\%$ of Calibrated FSO (Vacuum only [-23])	<b>Wetted Parts:</b>	
<b>Temperature Shift:</b>	Zero & Span: 0.0125% Per °F over the compensated temperature range	Sensor:	17-4 PH Stainless steel (more than 10k psi) 316L Stainless steel (up to 10k psi) 17-4 PH Stainless steel for -UL option (10k psi)
<b>Long Term Stability:</b>	$\pm 0.2\%$ FSO /year of calibration curve	Fitting:	17-4 PH Stainless steel (all ranges) 316L Stainless steel (optional: up to 10k psi)
<b>Typical Life Cycle:</b>	100 million cycles	<b>Media</b>	
<b>Proof Pressure:</b>	2X range for up to 7500 psi models 1.5X range for 7500 - 30000 psi models	General:	Gas, vapor, liquid and viscous fluids [-Z17]
<b>Input:</b>	Excitation voltage: 9 to 30 VDC	Corrosive and Acidic: (up to 10,000 psi)	316L stainless Steel fitting, NACE [-SS or -SC]
<b>Supply Current:</b>	20mA max.	<b>Pressure Connection:</b>	13 available options. Refer to product configurator for available connections and ranges.
<b>Output:</b> H455E:	Output: 4–20 mA with HART® Protocol Full Scale Output: 20 mA $\pm 1\%$ Zero output: 4 mA $\pm 1\%$	<b>Electrical Connection:</b>	10 available electrical connections such as M12, Bendix, DIN, conduit, gland and etc. Option for free leads from conduit or gland electrical connection includes two signal leads plus ground lead consisting of 18AWG halogen free type, 80" (2m) long or optional jacketed cable exiting 1/2 NPT or M20 conduit or gland connections.
455E:	Output: 4–20 mA Full Scale Output: 20 mA $\pm 1\%$ Zero output: 4 mA $\pm 1\%$	<b>Temperature Ranges:</b>	
<b>Dynamic Response Time:</b>	<70 milliseconds	Operating (Ambient):	-40 to +176 °F (-40 to +80 °C)
<b>Enclosure:</b>	All welded 300 series stainless steel. IP66 & IP67 and NEMA 4X rated. 316 Stainless Steel (optional)	Compensated:	0 to +165 °F (-18 to +74 °C)
		Media:	-40 to +176 °F (-40 to +80 °C)
		Storage:	-40 to +185 °F (-40 to +85 °C)
		<b>Vibration:</b>	10 g's, 10-500 Hz, MIL-STD 202, Method 204, Cond. A
		<b>Shock:</b>	50 g's, 11 mS, MIL-STD 202 Method 213, Cond. G.

\* See product configurator for additional options.

**Barksdale®**

Subject to technical changes.

# BiT – Barksdale Intelligent Transmitter *Series H455E, 455E, 452E, 454E*

## General Specifications\* cont.

<b>Approvals:</b> CSA	cCSAus Ordinary Locations
CSA	cCSAus Intrinsic Safety for Hazardous Locations Class I, Div. 1, Groups A, B, C & D Class II, Div. 1, Groups E, F & G Ex ia IIC T4 Ga Ex ia IIIC T135°C Da Class 1 Zone 0, AEx ia IIC T4 Ga Zone 20 AEx ia IIIC T135°C Da
<b>ATEX/IECEX:</b>	Factory sealed IP66 & IP67 and NEMA 4X enclosure  CE 0081 Ex II 1 G D Ex ia IIC T4 Ga Ex ia IIIC T135°C Da, IP66 & IP67 -40 °C ≤ Tamb ≤ +80 °C CML 19 ATEX 2240X IECEx CML 19.0066X
<b>HART® Protocol:</b>	HART® 7.6
Turndown Ratio:	10:1 (Full scale output rangeability)
Analog Output Calibration:	Adjustable zero and span of 4-20mA. Full scale range must be ≥ (calibrated span / 10)
Sensor Trim:	Sensor zero and full scale trim
Diagnostics:	Transmitter failure indicated by off-scale analog signals to alarm the user  See HART Installation and Operation Manual 272438 for detailed information

<b>Compliances:</b>	CE, NACE (316L SS)
<b>Electromagnetic Compatibility (EMC)</b>	
IEC/EN 55011:	Emission & radiated emission for class A limits
IEC/EN 61000-4-2:	Electrostatic discharge (ESD) test - contact discharge +/-4 kV, Air discharge +/-8 kV
IEC/EN 61000-4-3:	Radiated RF, EM field immunity 80mhz-1ghz, 3v/M
IEC/EN 61000-4-4:	EFT (Burst) Test, +/-2 kV
IEC/EN 61000-4-5:	Surge Test, +/-1kV between line and earth ground
IEC/EN 61000-4-6:	RF Immunity, 150 kHz – 80 MHz, 3V
<b>Weight:</b>	16 Ounces (453 grams)
<b>Warranty:</b>	1 year warranty

\* See product configurator for additional options.

Installation: Intrinsic Safety Installation for Hazardous Locations: Install per Barksdale Control Drawing 272471						
I.S. Entry Parameters	Type	Model	SUPPLY/SIGNAL BARRIER		Pressure Transmitter	
			Vmax (UI)	Imax	CI	LI
	Hart 4-20 mA	H455E	30 VDC	100 mA	2.2 nF	30 µH
Current Output	455E	30 VDC	100 mA	27.384 nF	0 µH	750 mW
Voltage Output	452E	30 VDC	100mA	54.984 nF	0 µH	750 mW
Ratiometric Output	454E	20VDC	100mA	46.320 nF	0 µH	750 mW

## Wiring Code


MODEL NO.	RED/A/1	BLACK/B/2	GREEN/D/4	WHITE WIRE/C/3
H455E	+ EXCITATION	- EXCITATION	EARTH GROUND	NOT INCLUDED
455E	+ EXCITATION	- EXCITATION	EARTH GROUND	NOT INCLUDED
425E	+ EXCITATION	- EXCITATION	EARTH GROUND	VOLTAGE OUTPUT
454E	+ EXCITATION	- EXCITATION	EARTH GROUND	RATIOMETRIC OUTPUT

MODEL NO.	WHITE	BROWN	GREEN	YELLOW
H455E	+ EXCITATION	- EXCITATION	EARTH GROUND	NOT INCLUDED
455E	+ EXCITATION	- EXCITATION	EARTH GROUND	NOT INCLUDED
452E	+ EXCITATION	- EXCITATION	EARTH GROUND	VOLTAGE OUTPUT
454E	+ EXCITATION	- EXCITATION	EARTH GROUND	RATIOMETRIC OUTPUT


MODEL	CONNECTOR	PIN A/1	PIN B/2	PIN C/3	PIN D/4
ALL	D3	+ EXCITATION	- EXCITATION	EARTH GROUND	N/A
ALL	D4	- EXCITATION	+ EXCITATION	EARTH GROUND	N/A



### CONFIGURATION WITH HART®



### Multi Drop



Subject to technical changes.

# Transmitter

## BiT – Barksdale Intelligent Transmitter

## Series H455E, 455E

### Technical Drawings

FACTORY SEALED HALOGEN FREE 18 AWG LEADS 80 INCHES (2 METERS) REFER TABLE 1 & 2.  
OPTIONAL: JACKETED CABLE (LEADS/CABLE: BLANK, -T6, -H3)

1/4" [6.4]

ELECTRICAL CONNECTIONS:  
STD(BLANK): 1/2"-14 NPT MALE CONDUIT THREADS

OPTIONAL:  
T2: BENDIX 6P, SS HERMETIC  
T3: BENDIX, 6P, ALUM. FLANGE  
T4: M12 (4 Pin) CONNECTOR  
T5: STD DIN (43650)  
T6: M20X1.5 THD  
T7: M8 (4 Pin) CONNECTOR  
T8: 4 PIN BENDIX, SS HERMETIC  
H3: WATERTIGHT GLAND WITH 18 AWG FREE LEADS  
H4: SUBMINATURE DIN (43650)

5 21/64" [135.4]

4 53/64" [122.7]

5" [127.7]

Ø .59 [15]

Ø 1 3/8" [35]

Ø .03 OR Ø3/16 PRESSURE PORT OPENING

1/4 NPT FEMALE THD (P6 SHOWN) REFER CONFIGURATION TABLE ON SHEET 2 FOR OPTIONAL PROCESS CONNECTIONS.

A/F 1" or 1 1/8" [25.4] or [28.6]

Ø 12 TERMINATION: BENDIX CONNECTOR MS3113 TYPE, 6 PIN, SS HERMETIC

DIMENSIONS IN BRACKET ARE IN MM

#### Standard and Optional Electrical Connections

T2: 6 PIN CONNECTOR, SS HERMETIC

T3: 6 PIN CONNECTOR, ALUM. FLANGE MOUNT

T4: M12, 4P CONNECTOR

T7: M8, 4P CONNECTOR

T5: STANDARD DIN CONNECTOR

H3: CABLE CONNECTOR

H4: SUBMINATURE DIN CONNECTOR

T8: 4 PIN CONNECTOR, SS HERMETIC

-D3 CONNECTOR OPTION

-D4 CONNECTOR OPTION WITH WATERTIGHT GLAND (H3)

LOOP RESISTANCE REQUIRED (OHMS)

EXCITATION VOLTAGE (volts DC)

MAXIMUM RESISTANCE

OPERATING BAND

#### Process Connections

G 1/2 M, -P11	G 1/2 E, -P13	7/16-20, W/ 37° Flared, M, -P3	7/16-20, W/ 37° Flared, F, -P1	7/16-20, SAE #4, ORB, M, -P2	7/16-20, SAE #4, ORB, F, -P14

# BiT – Barksdale Intelligent Transmitter

## Series H455E, 455E

### Product Configurator

Example: **H455E** **T6** **-29** **BA** **-P15** **-Z17-A1-Z123**

#### Base Model

<b>H455E</b>	4 - 20 mA Output with HART® Comm. Protocol
<b>455E</b>	4 - 20 mA Output
452E	1-10V V Output
454E	0.5-4.5V; Ratiometric Output

\* Highlighted options represent those most frequently used. Select these common options for improved availability. (5/21)

#### Electrical Connection

<b>Blank</b>	1/2"-14 NPT Male conduit
T2	6 pin connector, SS Hermetic, PTIH-10-6P
T3	6 pin connector, Alum. Flange Mount, PT02E-10-6P
<b>T4</b>	M12 (4 Pin) connector
T5	Standard DIN (EN 175301-803, Type A)
T6	M20 x 1.5 Male conduit
T7	M8 (4 Pin) connector
T8	4 pin connector, SS Hermetic, PTIH-14S-2P
H3	Watertight Gland with 18AWG Free Leads
H4	Mini DIN (EN 175301-803, Type C)

#### Pressure Unit & Type

<b>Blank</b>	PSI - Gauge pressure (standard)
<b>A</b>	PSI - Absolute pressure (Not applicable with "-23" range)
<b>B</b>	Bar - Gauge Pressure
<b>BA</b>	Bar - Absolute Pressure (ranges start from -1 Bar) (Not applicable with "-23" range)

#### Process Connection

<b>Blank<sup>4</sup></b>	1/4-18 NPT male (standard)
-P6 <sup>4</sup>	1/4" NPT female
-P4 <sup>4</sup>	1/2" NPT male
-P5 <sup>4</sup>	1/2" NPT female
-P10 <sup>4</sup>	G 1/4, washer seal, male
-P12 <sup>4</sup>	G 1/4, washer seal, female
-P11 <sup>4</sup>	G 1/2, washer seal, male
-P13 <sup>4</sup>	G 1/2, washer seal, female
-P3 <sup>4</sup>	7/16-20, with 37° flared, male
-P1 <sup>4</sup>	7/16-20, with 37° flared, female
-P2 <sup>4</sup>	7/16-20, SAE #4, ORB, male
-P14 <sup>4</sup>	7/16-20, SAE #4, ORB, female
-P15	HF4 Autoclave, 1/4" tube, female (9/16-18 UNF-2B THD)

#### Pressure Range

-23*	0-29.9" of Hg	0 to -1 Bar
-01	0-15 psi	0-1 Bar
-21	0-30 psi	0-2 Bar
-03	0-50 psi	0-3 Bar
-22	0-60 psi	0-4 Bar
-04	0-100 psi	0-7 Bar
-05	0-150 psi	0-10 Bar
-06	0-200 psi	0-15 Bar
-07	0-300 psi	0-20 Bar
<b>-08</b>	0-500 psi	0-40 Bar
<b>-10</b>	0-1,000 psi	0-70 Bar
<b>-11</b>	0-1,500 psi	0-100 Bar
<b>-12</b>	0-2,000 psi	0-150 Bar
<b>-13</b>	0-3,000 psi	0-200 Bar
<b>-14</b>	0-4,000 psi	0-300 Bar
<b>-15</b>	0-5,000 psi	0-350 Bar
<b>-16</b>	0-6,000 psi	0-400 Bar
<b>-17</b>	0-7,500 psi	0-500 Bar
<b>-18<sup>1</sup></b>	0-10,000 psi	0-700 Bar
<b>-29<sup>3</sup></b>	0-15,000 psi	0-1,000 Bar
<b>-30<sup>3</sup></b>	0-20,000 psi	0-1,400 Bar
<b>-31<sup>3</sup></b>	0-22,000 psi	0-1,500 Bar
<b>-32<sup>3</sup></b>	0-25,000 psi	0-1,700 Bar
<b>-33<sup>3</sup></b>	0-30,000 psi	0-2,000 Bar

#### Options

-ZVxx	Custom voltage output (Available on 452X only). Up to 10VDC. Consult Factory.
-Z17 <sup>2</sup>	For high pressure models with larger orifice; without pressure surge protector
-SC <sup>5</sup>	All 316 stainless steel construction with 316L SS wetted material (NACE)
-SS <sup>4,5</sup>	316L stainless steel wetted material (NACE)
-UL <sup>1</sup>	cCSAus approval, only for 10k psi "-18" range. Includes ATEX & IECEx approvals.
<b>-A1</b>	Accuracy BFSL 0.1% FSO (LHR) at 75°F (Consult factory on vacuum [-23] models)
-ZXXX	Special pressure ranges XX - significant digits Y - number of trailing zeros Example: 130 psi calibration: add -Z131
-JXXX	Jacketed cable (available on conduit and gland electrical connections) (in inches)
-WXXX	Custom Length of free leads (Available on Conduit and gland electrical connections) (In Inches)
-D3 <sup>6</sup>	3 Pin deutsch connector DT04-3P
-D4 <sup>6</sup>	4 Pin deutsch connector DT04-4P

#### Notes

- UL option only available for 10,000 psi range. No cCSAus approval for 10,000 psi range without -UL suffix option. cCSAus approval standard for all other ranges
- All pressure ranges have built-in pressure surge protector. Add "-Z17" suffix for high pressure models with no snubber; for use with high viscosity media. Refer to Sales drawing for orifice sizes.
- Ranges with more than 10k psi are only available with -P15 Process Connection
- Available up to 10,000 psi
- SS option is included in -SC option. -SC does not include material of electrical connection. -UL option and ranges that are more than 10k psi are only available with 17-4PH SS wetted material.
- Connected to factory sealed halogen free, 18 AWG free leads 12" (.3m). Also available with -WXXX and -JXXX options.

### Additional Documents & Accessories

Title	Reference Number
Installation and Maintenance Instructions, Control Drawing	272441, 272471
HART Installation and Operation Manual	272438
Cable & Connectors	Cable & Connectors. Bulletin #S0115-C
Certificate of Compliance (Found on back of packing slip)	Use Document Title in purchase order. Only available at the time of order.
Certificate of Compliance (Signed document)	
Test Report	
Calibration Test Sheet (Included in product package)	
Material Certification	
Paper Tag	
Metal Tag	

\* Vacuum

3211 Fruitland Avenue • Los Angeles, CA 90058 • ☎ 800-835-1060 • Fax: 323-589-3463 • www.barksdale.com

**Barksdale**  
CONTROL PRODUCTS

See Barksdale's Standard Conditions of Sale • Specifications are subject to modification at any time • Bulletin #S0050-C • 04/22 • ©2022 • Printed in the U.S.A.